

Use the "Select Text" tool
to Cut & Paste into your
document.



MASTER SPECS: SECTION 10435



Display hidden notes by using "Tools"/"Options"/"View"/"Hidden Text".

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Wall Mounted Frames.
- B. Projected Wall Bracket Mounted Frames.
- C. Directory Frames.
- D. Table Stands.
- E. Double Sided Pylons.
- F. Suspended Frames.
- G. Triangular Pylons.
- H. Vista Light System.

1.2 RELATED SECTIONS

- A. Section 15075 - Mechanical Identification.
- B. Section 16500 - Lighting.

1.3 REFERENCES

- A. ICC/ANSI A117.1 - Accessible and Useable Buildings and Facilities; 1998.
- B. USATBCB - Americans with Disabilities Act (ADA), Accessibility Guidelines for Buildings and Facilities (ADAAG).

1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. [[Product Data](#)]: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.
- C. Shop Drawings: Indicate sign styles, lettering, locations and dimensions of each interior sign.
- D. Selection Samples: For each finish product specified, two complete sets of color chips representing manufacturer's full range of available colors and patterns.
- E. Verification Samples: For each finish product specified, two samples, minimum size 6 inches (150 mm) square, representing actual product, color, and patterns.

1.5 QUALITY ASSURANCE

- A. Regulatory Requirements: Comply with requirements of ICC/ANSI A117.1 and ADAAG.

- B. Mock-Up: Provide a mock-up of each sign type for evaluation of mounting techniques and application workmanship.
 - 1. Locate in areas designated by Architect.
 - 2. Do not proceed with remaining work until workmanship approved by Architect.
 - 3. Reinstall mock-up signs as required to produce acceptable work.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Store products in unopened protective packaging until ready for installation.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: Vista System Inc.; 4545 Mariotti Ct., Unit C, Sarasota, FL 34233. ASD. Toll Free: 800-468-4782, Phone: 941-927-3312. Fax: 888-316-5198. Local Dealer: Purpose1 Identity Solutions, 2225 Sycamore St., Harrisburg, PA 17111. Phone: 717-232- 9077. Fax: 717-232-6040. Web Site: www.vistasystem.com , www.IDsolutions1.com.
- B. Substitutions: Not permitted.
- C. Requests for substitutions will be considered in accordance with provisions of Section 01600.

2.2 SIGNAGE

- A. Products: Provide the following interior sign system types in the locations and in the configurations indicated.
 - 1. Wall Mounted Frames: Wall-mounted signs with the Vista frame extrusions using any flat, flexible substrate to create a curved-face sign.
 - 2. Projecting Wall Bracket Mounted Frames: Double faced Vista frame extrusions designed to be wall mounted on projecting wall brackets.
 - 3. Directory Frames: Directories are wall-mounted signs with the Vista frame extrusions that are field assembled with insert materials as indicated.
 - 4. Table Stand Signage: Tables stands are a complete package including convex frame, aluminum base and end cap, clear/non glare lens.
 - 5. Double Sided Pylons: Double faced Vista frame extrusions designed to be floor mounted on free standing or fixed bases in the configuration indicated.
 - 6. Suspended Frames: Double faced Vista frame extrusions designed to be suspended as indicated.
 - 7. Double Sided Post Pylons: Double faced Vista frame extrusions designed to be post pylon signs with single or side-by-side posts that are floor mounted on free standing or fixed bases in the configuration indicated.
 - 8. Triangular Tower Pylons: Triple sided post pylon signs of Vista frame extrusions designed to be floor mounted on free standing or fixed bases in the configuration indicated.
 - 9. Vista Light System: Provide freestanding, convex, double sided signs that are backlit with the addition of interior illumination, or used with standard sign substrates without illumination. Designed to be floor mounted on free standing or fixed bases in the configuration indicated.
- B. **Sign Substrates and Inserts**
 - 1. Engraved Signs: Laminated colored plastic; lettering engraved through face to expose core color:

- a. Face Color: Color as selected.
 - b. Core Color: Color as selected.
 - c. Height: _____ inches (_____ mm).
 - d. Edges:
 - 1) Square to conform to sign frame interior space
 - e. Character Font: _____.
2. Engraved Signs: Laminated colored plastic with clear core; lettering reverse engraved through back and filled with paint color:
- a. Face Color: Color as selected.
 - b. Paint Color: Color as selected.
 - c. Height: _____ inches (_____ mm).
 - d. Edges:
 - 1) Square to conform to sign frame interior space
 - e. Character Font: _____.
3. Sand Blasted Signs: Acrylic high gloss plastic; letters sand blasted to dull sheen:
- a. Color: Color as selected.
 - b. Height: _____ inches (_____ mm).
 - c. Edges:
 - 1) Square to conform to sign frame interior space
 - d. Character Font: _____.
4. Silk Screened Signs: Letters _____ inch (_____ mm) high silk screened onto plastic surface:
- a. Sign Color: Color as selected.
 - b. Character Color: _____ color.
 - c. Height: _____ inches (_____ mm).
 - d. Edges:
 - 1) Square to conform to sign frame interior space
 - e. Character Font: _____.
5. Raised Letter Signs with Braille and optional graphics on acrylic plastic (ADA Sign).
- a. Base Acrylic Material:
 - 1) Sign material must have non-glare (matte) surface
 - a) Clear
 - b) Solid embedded color material
 - 2) Sign Color: Color as selected.
 - b. Height: _____ inches (_____ mm).
 - c. Edges:
 - 1) Square to conform to sign frame interior space
 - d. Raised Characters:
 - 1) Character Font: _____.
 - 2) Character Color: _____.
 - 3) Character Thickness: 1/32 inch (0.8 mm).
 - 4) Character Return Angle: 22 degrees.
 - 5) Character Adhesive: 3M Scotch 467HP adhesive.
 - e. Raised Graphics or Icons:
 - 1) Graphic Color: _____.
 - 2) Graphic Thickness: 1/32 inch (0.8 mm).
 - 3) Graphic Return Angle: 22 degrees.
 - 4) Graphic Adhesive: 3M Scotch 467HP adhesive.
 - f. Braille:
 - 1) Grade II Raster Braille with domed surface.
6. Provide signs with _____ Vista Key suction cup devices for removal of clear covers.

2.3 WALL MOUNTED FRAMES

- A. **Wall Frames - Portrait Series:** Extruded Aluminum of the sizes specified. This sign/product includes assembly.
1. Style/Size:
 - a. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches portrait height.
 - b. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches portrait height.
 - c. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches portrait height.
 - d. V200, overall radius width is 7.87 inches (200 mm). Size _____ inch portrait height.
 - e. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches portrait height.
 - f. VLetter, overall radius width is 8.50 inches (216 mm). Size _____ inches portrait height.
 - g. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches portrait height.
 - h. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 - i. V500, overall radius width is 19.68 inches (500 mm). Size _____ inches portrait height.
 - j. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches portrait height.
 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
 3. Clear cover for extrusion thick polycarbonate, glossy one side, non-glare one side.
 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
 5. Mounting:
 - a. Mechanical with all mounting holes predrilled.
 - b. Double faced tape.
 - c. Mechanical with primary mounting holes predrilled and set with silicone sealant.
- B. **Wall Frames - Landscape Series:** Extruded Aluminum of the sizes specified. This sign/product includes assembly.
1. Style/Size:
 - a. V60, overall radius width of 2.36 inches (60 mm). Size _____ inches landscape width.
 - b. V80, overall radius width is 3.15 inches (80 mm). Size _____ inches landscape width.
 - c. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches landscape width.
 - d. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches landscape width.
 - e. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches

- f. landscape width.
V200, overall radius width is 7.87 inches (200 mm). Size _____ inches landscape width.
 - g. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches landscape width.
 - h. VLetter, overall radius width is 8.50 inches (216 mm). Size _____ inches landscape width.
 - i. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches landscape width.
2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
 3. Clear cover for extrusion polycarbonate, glossy one side, non-glare one side.
 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
 5. Mounting:
 - a. Mechanical with all mounting holes predrilled.
 - b. Double faced tape.
 - c. Mechanical with primary mounting holes predrilled and set with silicone sealant.

2.4 PROJECTED WALL BRACKET MOUNTED FRAMES

- A. Projected Wall Bracket - Double Sided Portrait Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.
 1. Style/Size:
 - a. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches portrait height.
 - b. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches portrait height.
 - c. V200, overall radius width is 7.87 inches (200 mm). Size _____ inches portrait height.
 - d. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches portrait height.
 - e. V-Letter, overall radius width is 8.50 inches (216 mm). Size _____ inches portrait height.
 - f. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches portrait height.
 - g. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
 3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.

- b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 5. Wall Bracket:
 - a. Aluminum wall bracket - Deluxe type:
 - 1) Finish: Black powder coat.
 - 2) Finish: Custom Painted Colors _____.
 - b. Steel wall bracket - Standard type, painted color as selected.
 - 1) Finish: Black powder coat.
 - 2) Finish: Custom Painted Colors _____.
- 6. Mounting:
 - a. Mechanical with all mounting holes predrilled.
 - b. Double faced tape.

B. Projected Wall Bracket - Landscape Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

- 1. Style/Size:
 - a. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches landscape width.
 - b. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches landscape width.
 - c. V200, overall radius width is 7.87 inches (200 mm). Size _____ inches landscape width.
 - d. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches landscape width.
 - e. V-Letter, overall radius width is 8.50 inches (216 mm). Size _____ inches landscape width.
 - f. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches landscape width.
 - g. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches landscape width.
- 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
- 3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
- 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 5. Wall Bracket:
 - a. Aluminum wall bracket - Deluxe type:
 - 1) Finish: Black powder coat.
 - 2) Finish: Custom Painted Colors _____.
 - b. Steel wall bracket - Standard type, painted color as selected.
 - 1) Finish: Black powder coat.
 - 2) Finish: Custom Painted Colors _____.
- 6. Mounting:
 - a. Mechanical with all mounting holes predrilled.
 - b. Double faced tape.

- C. Projected Wall Bracket - Landscape Series with Simple Base: Extruded Aluminum of the sizes specified. This sign/product includes assembly.
1. Style/Size:
 - a. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches landscape width.
 - b. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches landscape width.
 - c. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches landscape width.
 - d. V200, overall radius width is 7.87 inches (200 mm). Size _____ inches landscape width.
 - e. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches landscape width.
 - f. V-Letter, overall radius width is 8.50 inches (216 mm). Size _____ inches landscape width.
 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
 3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
 4. End Caps for Extrusions: Provided with matching screws
 - a. Metal, double sided.
 - 1) Color: Black.
 - 2) Color: Gray.
 5. Aluminum wall bracket - Simple base type, Black (Paint).
 6. Mounting:
 - a. Mechanical with all mounting holes predrilled.
 - b. Double faced tape.

2.5 DIRECTORY FRAMES

- A. Directory Frames - Portrait Series: Extruded Aluminum of the sizes specified. All mounting holes are predrilled. This sign/product includes assembly.
1. Style/Size:
 - a. V300, overall radius width is 11.81 inches (300 mm).
 - 1) Overall directory height is _____ inches (_____ mm).
 - 2) Directory is divided into __ sections with one upper section at __ inches high and ___ lower sections at __ inches high each.
 - 3) Provide divider strips between each section.
 - b. V400, overall radius width is 15.74 inches (400 mm).
 - 1) Overall directory height is _____ inches (_____ mm).
 - 2) Directory is divided into __ sections with one upper section at __ inches high and ___ lower sections at __ inches high each.
 - 3) Provide divider strips between each section.
 - c. V500, overall radius width is 19.68 inches (500 mm).
 - 1) Overall directory height is _____ inches (_____ mm).
 - 2) Directory is divided into __ sections with one upper section at __ inches high and ___ lower sections at __ inches high each.
 - 3) Provide divider strips between each section.
 - d. V600, overall radius width is 25.62 inches (600 mm).
 - 1) Overall directory height is _____ inches (_____ mm).
 - 2) Directory is divided into __ sections with one upper section at __ inches high and ___ lower sections at __ inches high each.
 - 3) Provide divider strips between each section.
 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.

- b. Black Anodized.
- c. Custom Colors _____.
- 3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.
- 4. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
- 5. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.

B. Directory Frames - Landscape Series: Extruded Aluminum of the sizes specified. All mounting holes are predrilled. This sign/product includes assembly.

- 1. Style/Size:
 - a. V100/V60, overall radius width of 3.93 inches (100 mm) and 2.36 inches (60 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Directory is divided into __ sections with one upper section at __ inches wide and __ lower sections at __ inches high each.
 - 4) Provide divider strips between each section.
 - b. V150/V80, overall radius width is 5.90 inches (150 mm) and 3.15 inches (80 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Directory is divided into __ sections with one upper section at __ inches high and __ lower sections at __ inches high each.
 - 4) Provide divider strips between each section.
 - c. V200.V120, overall radius width is 7.87 inches (200 mm) and 4.72 inches (120 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Directory is divided into __ sections with one upper section at __ inches high and __ lower sections at __ inches high each.
 - 4) Provide divider strips between each section.
- 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
- 3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.
- 4. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
- 5. End Caps for Extrusions: Provided with matching screws

- a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- C. Directory Frames - Landscape/Portrait Combination Series: Extruded Aluminum of the sizes specified. All mounting holes are predrilled. This sign/product includes assembly.
1. Style/Size:
 - a. V60 with 4 VA4, overall radius width of 2.36 inches (60 mm) and 8.46 inches (215 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Lower directory is divided into 4 portrait units.
 - 4) Each lower directory unit is divided into __ sections with one upper section at __ inches wide and ____ lower sections at __ inches wide each.
 - 5) Provide divider strips between each section.
 - b. V60 with 4 VLetter, overall radius width of 2.36 inches (60 mm) and 8.50 inches (216 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Lower directory is divided into 4 portrait units.
 - 4) Each lower directory unit is divided into __ sections with one upper section at __ inches wide and ____ lower sections at __ inches wide each.
 - 5) Provide divider strips between each section.
 - c. V100 with 3 V400, overall radius width is 3.93 inches (100 mm) and 15.74 inches (400 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Lower directory is divided into 3 portrait units.
 - 4) Each lower directory unit is divided into __ sections with one upper section at __ inches wide and ____ lower sections at __ inches wide each.
 - 5) Provide divider strips between each section.
 - d. V80 with 3 V300, overall radius width is 3.15 inches (80 mm) and 11.81 inches (300 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Lower directory is divided into 3 portrait units.
 - 4) Each lower directory unit is divided into __ sections with one upper section at __ inches wide and ____ lower sections at __ inches wide each.
 - 5) Provide divider strips between each section.
 - e. V120 with 2 V500, overall radius width is 4.72 inches (120 mm) and 19.68 inches (500 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Lower directory is divided into 2 portrait units.
 - 4) Each lower directory unit is divided into __ sections with one upper section at __ inches wide and ____ lower sections at __ inches wide each.

- 5) Provide divider strips between each section.
- f. V200 with 2 V600, overall radius width is 7.87 inches (200 mm) and 23.62 inches (600 mm) respectively.
 - 1) Size _____ inch overall landscape width.
 - 2) Overall directory height is _____ inches (_____ mm).
 - 3) Lower directory is divided into 2 portrait units.
 - 4) Each lower directory unit is divided into ___ sections with one upper section at ___ inches wide and ___ lower sections at ___ inches wide each.
 - 5) Provide divider strips between each section.
2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.
4. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
5. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.

2.6 TABLE STANDS

- A. Table Stand - Kangaroo (Portrait) Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.
 1. Style/Size:
 - a. V60, overall radius width is 2.36 inches (60 mm). Size _____ inches overall portrait height.
 - b. V80, overall radius width is 3.15 inches (80 mm). Size _____ inches overall portrait height.
 - c. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches overall portrait height.
 - d. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches overall portrait height.
 - e. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches overall portrait height.
 - f. V200, overall radius width is 7.87 inches (200 mm). Size _____ inches overall portrait height.
 - g. VLetter, overall radius width is 8.50 inches (216 mm). Size _____ inches overall portrait height.
 - h. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches overall portrait height.
 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.

3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Paint.
 - 3) Finish: Custom Colors _____.
5. Aluminum base for Kangaroo style tabletop design.
 - 1) Clear Anodized.
 - 2) Gold Anodized.
 - 3) Black Anodized.
 - 4) Custom Colors _____.

B. Table Stand - Boomerang (Landscape) Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

1. Style/Size:
 - a. V60, overall radius width is 2.36 inches (60 mm). Size _____ inches overall landscape width.
 - b. V80, overall radius width is 3.15 inches (80 mm). Size _____ inches overall landscape width.
 - c. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches overall landscape width.
 - d. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches overall landscape width.
 - e. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches overall landscape width.
 - f. V200, overall radius width is 7.87 inches (200 mm). Size _____ inches overall landscape width.
 - g. VLetter, overall radius width is 8.50 inches (216 mm). Size _____ inches overall landscape width.
2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
4. End Caps for Extrusions: Provided with matching screws
 - a. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Gold Anodized.
 - 3) Finish: Black Paint.
 - 4) Finish: Custom Colors _____.
5. Aluminum base for Kangaroo style tabletop design.
 - 1) Clear Anodized.
 - 2) Black Anodized.
 - 3) Custom Colors _____.

C. Table Stand - Triangle (Landscape) Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

1. Style/Size:
 - a. TS30, Size _____ inches overall landscape width.
2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.

3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.

2.7 DOUBLE SIDED PYLONS

A. Double Sided Pylon: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

1. Style/Size:
 - a. VA4, overall radius width is 8.46 inches (215 mm).
 - 1) Design:
 - a) Slim.
 - b) Wide.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ____ inches (____ mm).
 - 4) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) ____ lower section(s) at __ inches high each.
 - 5) Provide divider strips between each section.
 - b. V Letter, overall radius width is 8.50 inches (216 mm).
 - 1) Design:
 - a) Slim.
 - b) Wide.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ____ inches (____ mm).
 - 4) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) ____ lower section(s) at __ inches high each.
 - 5) Provide divider strips between each section.
 - c. V300, overall radius width is 11.81 inches (300 mm).
 - 1) Design:
 - a) Slim.
 - b) Wide.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ____ inches (____ mm).
 - 4) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) ____ lower section(s) at __ inches high each.
 - 5) Provide divider strips between each section.
 - d. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 - 1) Design:

- a) Slim.
 - b) Wide.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ____ inches (____ mm).
 - 4) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) ____ lower section(s) at __ inches high each.
 - 5) Provide divider strips between each section.
 - e. V500, overall radius width is 19.68 inches (500 mm).
 - 1) Design:
 - a) Slim.
 - b) Wide.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ____ inches (____ mm).
 - 4) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) ____ lower section(s) at __ inches high each.
 - 5) Provide divider strips between each section.
 - f. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches portrait height.
 - 1) Design:
 - a) Slim.
 - b) Wide.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ____ inches (____ mm).
 - 4) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) ____ lower section(s) at __ inches high each.
 - 5) Provide divider strips between each section.
2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
 3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.
 4. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
 5. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.

- 2) Color: Gray.
- b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 6. Steel base:
 - a. Free standing units, oval shaped base:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - b. Floor mounted units:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - c. Finish:
 - 1) Black (Paint).
 - 2) Optional Color: _____.

2.8 SUSPENDED FRAMES

- A. Suspended Sign - Double Sided Landscape Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.
 - 1. Style/Size:
 - a. V60, overall radius width of 2.36 inches (60 mm). Size _____ inches landscape width.
 - b. V80, overall radius width is 3.15 inches (80 mm). Size _____ inches landscape width.
 - c. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches landscape height.
 - d. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches landscape height.
 - e. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches landscape height.
 - f. V200, overall radius width is 7.87 inches (200 mm). Size _____ inches landscape height.
 - g. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches landscape height.
 - h. V-Letter, overall radius width is 8.50 inches (216 mm). Size _____ inches landscape height.
 - i. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches landscape height.
 - j. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches landscape height.
 - k. V500, overall radius width is 19.68 inches (500 mm). Size _____ inches landscape height.
 - l. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches landscape height.
 - 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
 - 3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
 - 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.

- 2) Finish: Black Anodized.
- 3) Finish: Custom Painted Colors _____.
- 5. Stainless steel suspension cables, two at ___ feet (___ mm) long.
- 6. Cable clamps.
- 7. Ceiling cable fastener, silver.

B. Suspended Sign - Double Sided Landscape Multi-Tier Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

- 1. Style/Size:
 - a. V60, overall radius width of 2.36 inches (60 mm).
 - 1) Overall depth of _____ inches.
 - 2) Size _____ inches landscape width.
 - b. V80, overall radius width is 3.15 inches (80 mm).
 - 1) Overall depth of _____ inches.
 - 2) Size _____ inches landscape width.
 - c. V100, overall radius width is 3.93 inches (100 mm).
 - 1) Overall depth of _____ inches.
 - 2) Size _____ inches landscape width.
 - d. V120, overall radius width is 4.72 inches (120 mm).
 - 1) Overall depth of _____ inches.
 - 2) Size _____ inches landscape width.
 - e. V150, overall radius width is 5.90 inches (150 mm).
 - 1) Overall depth of _____ inches.
 - 2) Size _____ inches landscape width.
 - f. V80 / 2 V60, overall radius width is 3.15 inches (80 mm) and 2.36 inches (60 mm) respectively.
 - 1) Overall depth of 7.87 inches (200 mm) with one upper V80 and 2 V60 lower radius width frames.
 - 2) Size _____ inches landscape width.
 - g. V200, overall radius width is 7.87 inches (200 mm).
 - 1) Overall depth of 15.74 inches (400 mm) with two V200 radius width frames.
 - 2) Size _____ inches landscape width.
 - h. VA4, overall radius width is 8.46 inches (215 mm).
 - 1) Overall depth of 16.92 inches (430 mm) with two VA4 radius width frames.
 - 2) Size _____ inches landscape width.
 - i. V200 / 2 V120, overall radius width is 7.87 inches (200 mm) and 4.72 inches (120 mm) respectively.
 - 1) Overall depth of 17.31 inches (440 mm) with one upper V200 and 2 lower V120 radius width frames.
 - 2) Size _____ inches landscape width.
 - j. VA4 / 2 V120, overall radius width is 8.46 inches (215 mm) and 4.72 inches (120 mm) respectively.
 - 1) Overall depth of 17.90 inches (455 mm) with one upper VA4 and 2 lower V120 radius width frames.
 - 2) Size _____ inches landscape width.
 - k. V-Letter, overall radius width is 8.50 inches (216 mm).
 - 1) Overall depth of 17 inches (432 mm) with two radius width frames.
 - 2) Size _____ inches landscape width.
 - l. V-Letter / 2 V120, overall radius width is 8.50 inches (216 mm). and 4.72 inches (120 mm) respectively.
 - 1) Overall depth of 17.94 inches (456 mm) with one upper VLetter and two lower V120 radius width frames.
 - 2) Size _____ inches landscape width.

2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
5. Stainless steel suspension cables, two at ___ feet (___ mm) long.
6. Cable clamps.

C. Suspended Sign - Double Sided Portrait Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

1. Style/Size:
 - a. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 - b. V500, overall radius width is 19.68 inches (500 mm). Size _____ inches portrait height.
 - c. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches portrait height.
2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
4. End Caps for Extrusions: Provided with matching screws
 - a. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
5. Stainless steel suspension cables, two at ___ feet (___ mm) long.
6. Cable clamps.
7. Ceiling cable fastener, silver.

D. Suspended Sign - Double Sided Landscape Vista Light Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

1. Style/Size:
 - a. V250, overall radius width is 10.00 inches (250 mm). Size _____ inches landscape height.
 - b. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches landscape height.
 - c. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches landscape height.
 - d. V500, overall radius width is 19.68 inches (500 mm). Size _____ inches landscape height.
 - e. V600, overall radius width is 24.00 inches (600 mm). Size _____ inches landscape height.
 - f. V700, overall radius width is 28.00 inches (700 mm). Size _____ inches landscape height.
2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.

- b. Black Anodized.
- c. Custom Colors _____.
- 3. Cover for extrusion, polycarbonate:
 - a. Clear, glossy one side, non-glare one side.
 - b. White translucent, glossy one side, non-glare one side.
- 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 5. Stainless steel suspension cables, two at ___ feet (___ mm) long.
- 6. Cable clamps.
- 7. Ceiling cable fastener, silver.

E. Suspended Sign - Double Sided Portrait Vista Light Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

- 1. Style/Size:
 - a. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches Portrait height.
 - b. V500, overall radius width is 19.68 inches (500 mm). Size _____ inches Portrait height.
 - c. V600, overall radius width is 24.00 inches (600 mm). Size _____ inches Portrait height.
 - d. V700, overall radius width is 28.00 inches (700 mm). Size _____ inches Portrait height.
- 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
- 3. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
- 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 5. Stainless steel suspension cables, two at ___ feet (___ mm) long.
- 6. Cable clamps.
- 7. Ceiling cable fastener, silver.

2.9 POST PYLONS

A. Double Sided Post Pylons: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

- 1. Style/Size:
 - a. VA4, overall radius width is 8.46 inches (215 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is _____ inches (_____ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:

- a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - c) Post at ___ inches high.
 - 4) Provide divider strips between each section.
- b. V Letter, overall radius width is 8.50 inches (216 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ___ inches (___ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - c) Post at ___ inches high.
 - 4) Provide divider strips between each section.
- c. V300, overall radius width is 11.81 inches (300 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ___ inches (___ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - c) Post at ___ inches high.
 - 4) Provide divider strips between each section.
- d. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ___ inches (___ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - d) Post at ___ inches high.
 - 4) Provide divider strips between each section.
- e. V500, overall radius width is 19.68 inches (500 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ___ inches (___ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - d) Post at ___ inches high.
 - 4) Provide divider strips between each section.
- f. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches portrait height.
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ___ inches (___ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.

- c) ___ section(s) at ___ inches high.
 - d) Post at ___ inches high.
 - 4) Provide divider strips between each section.
- 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
- 3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.
- 4. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
- 5. End Caps for Extrusions: Provided with matching screws
 - a. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 6. Steel base:
 - a. Free standing units, oval shaped base:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - b. Floor mounted units:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - 3) Recessed sleeve mount.
 - c. Finish:
 - 1) Black (Paint).
 - 2) Optional Color: _____.

B. Triangular Post Pylons: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

- 1. Style/Size, Floor Mounted:
 - a. V200, overall radius width is 7.87 inches (200 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is _____ inches (_____ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - d) Post at ___ inches high.
 - 4) Provide divider strips between each section.
 - b. VA4, overall radius width is 8.46 inches (215 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is _____ inches (_____ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - d) Post at ___ inches high.

- 4) Provide divider strips between each section.
- c. V Letter, overall radius width is 8.50 inches (216 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ____ inches (____ mm).
 - 3) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) Post at __ inches high.
 - 4) Provide divider strips between each section.
- d. V300, overall radius width is 11.81 inches (300 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ____ inches (____ mm).
 - 3) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) Post at __ inches high.
 - 4) Provide divider strips between each section.
- e. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ____ inches (____ mm).
 - 3) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) Post at __ inches high.
 - 4) Provide divider strips between each section.
- f. V500, overall radius width is 19.68 inches (500 mm).
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ____ inches (____ mm).
 - 3) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.
 - d) Post at __ inches high.
 - 4) Provide divider strips between each section.
- g. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches portrait height.
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ____ inches (____ mm).
 - 3) Sign is divided into __ sections from top to bottom as follows:
 - a) ____ upper post mounted section at __ inches high.
 - b) ____ upper section(s) at __ inches high.
 - c) ____ section(s) at __ inches high.

- d) Post at ___ inches high.
 - 4) Provide divider strips between each section.
 - h. V700, overall radius width is 28.00 inches (700 mm). Size _____ inches portrait height.
 - 1) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 2) Overall sign height is ___ inches (___ mm).
 - 3) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - d) Post at ___ inches high.
 - 4) Provide divider strips between each section.
2. Aluminum Frame, Post Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.
4. Clear cover for extrusion, polycarbonate, glossy one side, non-glare one side.
5. End Caps for Extrusions: Provided with matching screws
 - a. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
6. Steel base for triangle sign:
 - a. Free standing units, oval shaped base:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - b. Floor mounted units:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - 3) Recessed sleeve mount.
 - c. Finish:
 - 1) Black (Paint).
 - 2) Optional Color: _____.

2.10 TRIANGULAR TOWER PYLONS

- A. Triangular Tower Signs: Extruded Aluminum of the sizes specified. This sign/product includes assembly.
 - 1. Style/Size:
 - a. VA4, overall radius width is 8.46 inches (215 mm).
 - 1) Sign has three equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section(s) at ___ inches high.

- b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- b. V Letter, overall radius width is 8.50 inches (216 mm).
 - 1) Sign has three equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section(s) at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- c. V300, overall radius width is 11.81 inches (300 mm).
 - 1) Sign has three equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section(s) at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- d. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 - 1) Sign has three equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section(s) at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- e. V500, overall radius width is 19.68 inches (500 mm).
 - 1) Sign has three equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper post mounted section(s) at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- f. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches portrait height.
 - 1) Sign has three equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:

- a) ___ upper post mounted section(s) at ___ inches high.
 - b) ___ upper section(s) at ___ inches high.
 - c) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
- 3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.
- 4. Clear cover for extrusion, thick polycarbonate, glossy one side, non-glare one side.
- 5. End Caps for Extrusions: Provided with matching screws
 - a. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 6. Steel base for triangle design three sided sign:
 - a. Free standing units, oval shaped base:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - b. Floor mounted units:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - c. Finish:
 - 1) Black (Paint).
 - 2) Optional Color: _____.

2.11 VISTA LIGHT SYSTEM

- A. Vista Light Double Sided Signs: Extruded aluminum, double sided sign holder of the sizes specified.
 - 1. Style/Size:
 - a. VL250, overall width is 12.30 inches (315 mm) and insert width is 10 inches (254 mm).
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
 - b. VL300, overall width is 14.30 inches (365 mm) and insert width is 12.00 inches (305 mm).
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is ___ inches (___ mm).

- 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
- 5) Provide divider strips between each section.
- c. VL400, overall width is 18.10 inches (462 mm) and insert width is 16.00 inches (406 mm). Size _____ inches portrait height.
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- d. VL500, overall width is 23.20 inches (592 mm) and insert width is 20.00 inches (508 mm).
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- e. VL600, overall width is 27.1 inches (692 inches) and insert width is 24.00 inches (610 mm). Size _____ inches portrait height.
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- f. VL700, overall width is 31 inches (790 mm) and insert width is 28.00 inches (710 mm). Size _____ inches portrait height.
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- g. VL800, overall width is 36.30 inches (924 mm) and insert width is 32.00 inches (812 mm). Size _____ inches portrait height.
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:

- a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- h. VL900, overall width is 40.2 inches (1024 mm) and insert width is 36.00 inches (914 mm). Size _____ inches portrait height.
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- i. VL1000, overall width is 44.10 inches (1123 mm) and insert width is 40.00 inches (1016 mm). Size _____ inches portrait height.
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.
- j. VL1200, overall width is 53.30 inches (1320 mm) and insert width is 48.00 inches (1219 mm). Size _____ inches portrait height.
 - 1) Sign has two equal sides.
 - 2) Type:
 - a) Floor Mounted.
 - b) Free Standing.
 - 3) Overall sign height is _____ inches (_____ mm).
 - 4) Sign is divided into ___ sections from top to bottom as follows:
 - a) ___ upper section(s) at ___ inches high.
 - b) ___ section(s) at ___ inches high.
 - 5) Provide divider strips between each section.

- 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.

- 3. Divider Strip Color:
 - a. Black.
 - b. Blue.
 - c. Silver.
 - d. Yellow.
 - e. White.
 - f. Custom Colors _____.

- 4. Cover for extrusion, polycarbonate:
 - a. Clear, glossy one side, non-glare one side.
 - b. White translucent, glossy one side, non-glare one side.

- 5. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.

- 2) Finish: Black Anodized.
- 3) Finish: Custom Painted Colors _____.
- 6. Steel base:
 - a. Free standing units, oval shaped base:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - b. Floor mounted units:
 - 1) Slim design for double sided sign.
 - 2) Wide design for double sided sign.
 - c. Finish:
 - 1) Black (Paint).
 - 2) Optional Color: _____.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Locate signs in accordance with approved shop drawings and ADA requirements.
- C. Install signs after surfaces to receive signage are finished.

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

SAMPLE SCHEDULE (Edit as Needed)

Room ID	Vista Stock #	Size	Mounting/Location	Copy/Remarks
Office Doors	WFP22U	Helvetica/1 inch	Door	Room Name/Black Face White Letters
Service Rooms	WFP22U	Helvetica/1 inch	Door	Room Name/Black Face White Letters
Rest Rooms	WFP25U	Helvetica/1 inch	Door	3 inch Graphic/Men, Woman Black Face White Letters

For Questions and More Information Call Mike at 800.318.9070



Division of:
Purpose1, Inc.
 2225 Sycamore Street
 Harrisburg, PA 17111

717.232.9077
 717.232.6040 fax

mike@purpose1.com

www.IDsolutions1.com