

Use the "Select Text" tool
to Cut & Paste into your
document.



WALL MOUNTED FRAMES

DESCRIPTION

Wall Mounted Frames: Wall-mounted signs with the Vista frame extrusions using any flat, flexible substrate to create a curved-face sign.

MANUFACTURERS

- A. Acceptable Manufacturer: Vista System Inc.; 4545 Mariotti Ct., Unit C, Sarasota, FL 34233. ASD. Toll Free: 800-468-4782, Phone: 941-927-3312. Fax: 888-316-5198. Local Dealer: Purpose1 Identity Solutions, 2225 Sycamore St., Harrisburg, PA 17111. Phone: 717-232- 9077. Fax: 717-232-6040. Web Site: www.vistasystem.com , www.idsolutions1.com .
- B. Substitutions: Not permitted.
- C. Requests for substitutions will be considered in accordance with provisions of Section 01600.

WALL MOUNTED FRAMES

- A. Wall Frames - Portrait Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.
 - 1. Style/Size:
 - a. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches portrait height.
 - b. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches portrait height.
 - c. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches portrait height.
 - d. V200, overall radius width is 7.87 inches (200 mm). Size _____ inch portrait height.
 - e. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches portrait height.
 - f. VLetter, overall radius width is 8.50 inches (216 mm). Size _____ inches portrait height.
 - g. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches portrait height.
 - h. V400, overall radius width is 15.74 inches (400 mm). Size _____ inches portrait height.
 - i. V500, overall radius width is 19.68 inches (500 mm). Size _____ inches portrait height.
 - j. V600, overall radius width is 23.62 inches (600 mm). Size _____ inches portrait height.
 - 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.

- c. Custom Colors _____.
- 3. Clear cover for extrusion thick polycarbonate, glossy one side, non-glare one side.
- 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 5. Mounting:
 - a. Mechanical with all mounting holes predrilled.
 - b. Double faced tape.
 - c. Mechanical with primary mounting holes predrilled and set with silicone sealant.

B. Wall Frames - Landscape Series: Extruded Aluminum of the sizes specified. This sign/product includes assembly.

- 1. Style/Size:
 - a. V60, overall radius width of 2.36 inches (60 mm). Size _____ inches landscape width.
 - b. V80, overall radius width is 3.15 inches (80 mm). Size _____ inches landscape width.
 - c. V100, overall radius width is 3.93 inches (100 mm). Size _____ inches landscape width.
 - d. V120, overall radius width is 4.72 inches (120 mm). Size _____ inches landscape width.
 - e. V150, overall radius width is 5.90 inches (150 mm). Size _____ inches landscape width.
 - f. V200, overall radius width is 7.87 inches (200 mm). Size _____ inches landscape width.
 - g. VA4, overall radius width is 8.46 inches (215 mm). Size _____ inches landscape width.
 - h. VLetter, overall radius width is 8.50 inches (216 mm). Size _____ inches landscape width.
 - i. V300, overall radius width is 11.81 inches (300 mm). Size _____ inches landscape width.
- 2. Aluminum Frame Finish:
 - a. Silver, Clear Anodized.
 - b. Black Anodized.
 - c. Custom Colors _____.
- 3. Clear cover for extrusion polycarbonate, glossy one side, non-glare one side.
- 4. End Caps for Extrusions: Provided with matching screws
 - a. Plastic (ABS).
 - 1) Color: Black.
 - 2) Color: Gray.
 - b. Metal: Brushed aluminum.
 - 1) Finish: Clear Anodized.
 - 2) Finish: Black Anodized.
 - 3) Finish: Custom Painted Colors _____.
- 5. Mounting:
 - a. Mechanical with all mounting holes predrilled.
 - b. Double faced tape.
 - c. Mechanical with primary mounting holes predrilled and set with silicone sealant.

EXECUTION

A. EXAMINATION

1. Do not begin installation until substrates have been properly prepared.
2. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

B. PREPARATION

1. Clean surfaces thoroughly prior to installation.
2. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

C. INSTALLATION

1. Install in accordance with manufacturer's instructions.
2. Locate signs in accordance with approved shop drawings and ADA requirements.
3. Install signs after surfaces to receive signage are finished.

D. PROTECTION

1. Protect installed products until completion of project.
2. Touch-up, repair or replace damaged products before Substantial Completion.

SAMPLE SCHEDULE (Edit as Needed)

Room ID	Vista Stock #	Size	Mounting/Location	Copy/Remarks
Office Doors	WFP22U	Helvetica/1 inch	Door	Room Name/Black Face White Letters
Service Rooms	WFP22U	Helvetica/1 inch	Door	Room Name/Black Face White Letters
Rest Rooms	WFP25U	Helvetica/1 inch	Door	3 inch Graphic/Men, Woman Black Face White Letters

For Questions and More Information Call Mike at 800.318.9070



Division of:
Purpose1, Inc.
2225 Sycamore Street
Harrisburg, PA 17111

717.232.9077
717.232.6040 fax

mike@purpose1.com

www.IDsolutions1.com